

HCS-4390N/03 Wireless Voting Unit



Technical Specifications

Mechanical

Dimensions (h x w x d).....	29 × 183 × 51 mm
Weight.....	0.2 kg
Color.....	Gray

Ordering Information

HCS-4390N/03.....	Wireless Voting Unit (portable, 3 voting keys, LCD display, gray)
-------------------	---

Features

- Portable, stylish and ergonomic design
- Wireless digital communication, adopting multilevel error correction and encrypted coding for high confidentiality and low error rate
- Voting unit will upload data on its time slot, this communication type is faster than roll polling. It takes about 1 second for 100 voting units uploading data
- When powered on, voting unit will search RF channel and join in the eligible RF channel automatically
- RF transceiving range: 100 m (frequency optional)
- Max. system capacity: 1200 wireless voting units
- 3 voting keys
- Multifunction voting in combination with the corresponding software modules:
 - ⌚ For/Against
 - ⌚ Parliamentary: YES/NO/ABSTAIN
 - ⌚ Questionnaire: 1~N
 - ⌚ Audience response: 0/25/50/75/100
 - ⌚ Score: 0~100
 - ⌚ Appraisal:
 - satisfied (Three keys voting: satisfied/basically satisfied/unsatisfied)
 - (Two keys voting: satisfied/unsatisfied)
 - Qualified (three/two keys voting)
 - Competent (three/two keys voting)
- Multiple proposal (maximum 10) voting function
- Large LCD for displaying voting and sign-in information, easy to use
- Screen backlight can be turned on/off by software
- Key-press sign-in
- Battery type (AA battery / Ni-MH rechargeable battery) can be configured by operator through software
- Two alkaline batteries (AA battery) for continuous using not less than 120 hours

HCS-4390NK/03 Wireless Voting Unit with IC-Card Reader



Technical Specifications

Mechanical

Dimensions (h x w x d)	29 × 183 × 51 mm
Weight	0.2 kg
Color	Gray

Ordering Information

HCS-4390NK/03	Wireless Voting Unit (portable, 3 voting keys, LCD display, IC-Card, gray)
---------------	--

Features

- Portable, stylish and ergonomic design
- Wireless digital communication, adopting multilevel error correction and encrypted coding for high confidentiality and low error rate
- Voting unit will upload data on its time slot, this communication type is faster than roll polling. It takes about 1 second for 100 voting units uploading data
- When powered on, voting unit will search RF channel and join in the eligible RF channel automatically
- RF transceiving range: 100 m (frequency optional)
- Max. system capacity: 1200 wireless voting units
- 3 voting keys
- Built-in IC-Card reader
- Multifunction voting in combination with the corresponding software modules:
 - ⊙ For/Against
 - ⊙ Parliamentary: YES/NO/ABSTAIN
 - ⊙ Questionnaire: 1~N
 - ⊙ Audience response: 0/25/50/75/100
 - ⊙ Score: 0~100
 - ⊙ Appraisal:
 - satisfied (Three keys voting: satisfied/basically satisfied/unsatisfied)
 - (Two keys voting: satisfied/unsatisfied)
 - Qualified (three/two keys voting)
 - Competent (three/two keys voting)
- Multiple proposal (maximum 10) voting function
- Large LCD for displaying voting and sign-in information, easy to use
- Screen backlight can be turned on/off by software
- Key-press sign-in
- Battery type (AA battery / Ni-MH rechargeable battery) can be configured by operator through software
- Two alkaline batteries (AA battery) for continuous using not less than 120 hours

HCS-4390N/10 Wireless Voting Unit



Technical Specifications

Mechanical

Dimensions (h x w x d).....	29 × 183 × 51 mm
Weight.....	0.2 kg
Color.....	Gray

Ordering Information

HCS-4390N/10.....	Wireless Voting Unit (portable, 10 voting keys, LCD display, gray)
-------------------	--

Features

- Portable, stylish and ergonomic design
- Wireless digital communication, adopting multilevel error correction and encrypted coding for high confidentiality and low error rate
- Voting unit will upload data on its time slot, this communication type is faster than roll polling. It takes about 1 second for 100 voting units uploading data
- When powered on, voting unit will search RF channel and join in the eligible RF channel automatically
- RF transceiving range: 100 m (frequency optional)
- Max. system capacity: 1200 wireless voting units
- 10 voting keys (0~9), “←” (confirm) key, “C” (cancel) key
- Multifunction voting in combination with the corresponding software modules:
 - ⊙ For/Against
 - ⊙ Parliamentary: YES/NO/ABSTAIN
 - ⊙ Multi-choice: 1~N
 - ⊙ Audience response: 0/25/50/75/100
 - ⊙ Score: 0~100
 - ⊙ Appraisal:
 - satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Multiple proposal (maximum 10) voting function
- Large LCD for displaying voting and sign-in information, easy to use
- Screen backlight can be turned on/off by software
- Key-press sign-in
- Battery type (AA battery / Ni-MH rechargeable battery) can be configured by operator through software
- Two alkaline batteries (AA battery) for continuous using not less than 120 hours

HCS-4390NK/10 Wireless Voting Unit with IC-Card Reader



Technical Specifications

Mechanical

Dimensions (h x w x d)	29 × 183 × 51 mm
Weight	0.2 kg
Color	Gray

Ordering Information

HCS-4390NK/10.....	Wireless Voting Unit (portable, 10 voting keys, LCD display, IC-Card, gray)
--------------------	---

Features

- Portable, stylish and ergonomic design
- Wireless digital communication, adopting multilevel error correction and encrypted coding for high confidentiality and low error rate
- Voting unit will upload data on its time slot, this communication type is faster than roll polling. It takes about 1 second for 100 voting units uploading data
- When powered on, voting unit will search RF channel and join in the eligible RF channel automatically
- RF transceiving range: 100 m (frequency optional)
- Screen backlight can be turned on/off by software
- Max. system capacity: 1200 wireless voting units
- 10 voting keys (0~9), “←” (confirm) key, “C” (cancel) key
- Built-in IC-Card reader
- Multifunction voting in combination with the corresponding software modules:
 - ☉ For/Against
 - ☉ Parliamentary: YES/NO/ABSTAIN
 - ☉ Multi-choice: 1~N
 - ☉ Audience response: 0/25/50/75/100
 - ☉ Score: 0~100
 - ☉ Appraisal:
 - satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Multiple proposal (maximum 10) voting function
- Large LCD for displaying voting and sign-in information, easy to use
- Screen backlight can be turned on/off by software
- Key-press sign-in
- Battery type (AA battery / Ni-MH rechargeable battery) can be configured by operator through software
- Two alkaline batteries (AA battery) for continuous using not less than 120 hours

HCS-4390KS Wireless Voting Unit Storage Case



Features

- Used for storing and transporting HCS-4390N series Wireless Voting Unit
- Every case can store up to 50 HCS-4390N Wireless Voting Units

Technical Specifications

Mechanical

Dimensions h x w x d (mm)..... 238 × 546 × 406
 Net weight..... 7.4 kg (w/o 1 HCS-4390N)
 Gross weight..... 17.4kg (w/50 pcs HCS-4390N, w/o battery)
 Color..... Blue

Ordering Information

HCS-5100KS..... Wireless Voting Unit Storage Case (50 pcs/case)